

# Multiple gas detector for Oxygen, Flammable Gases, Hydrogen sulphide GOMH-3A

One unit performs three roles, realizing highly efficient and safe control at the same time.

Can simultaneously measure three gases: oxygen, a flammable gas, and hydrogen sulphide.

- Simultaneous measurement of oxygen, flammable gases(non-methane), hydrogen sulphide
- Small / compact and lightweight
- Low power consumption design
- With Light & flow rate check function



## Specifications

Target gas	Oxygen	Combustible gas	Hydrogen sulphide
Measurement range	0 - 25 %	0 - 100 %LEL	0 - 30 ppm
Measurement principle	Galvanic cell method	Combustion contact	Controlled potential electrolysis
Sampling method	Diaphragm pump		
Display	Digital LCD (backlit)		
Indicating accuracy	+/- 0.5 %	5 % of full scale	
Alarm threshold	<18 %	>20 %LEL	>10 ppm
Alarm signal	Short, intermittent sound and blinking alarm light		
Operating Temperature	-10 - 40 °C		
Power source	Four size C dry cell batteries for approx. 4 hours of operation(without alarm signal being emitted)		
Dimensions	150(W) x 70(D) x 170(H) mm		
Weight	1.2kg		

\*The products may not be sold depending on countries and regions.

## Options



[Extension Hose 1365A-5/1365A-10/1365A-15/1365A-20](#)

Easy attachment or removal with one-touch coupler.  
Available in lengths of 5m, 10m, 15m, 20m.