

GNTU 764/102

GNTU 764/104

GNTU 764/108

# EFM G.SHDSL.bis



- Interoperability with GNTU 764/40x series
- Point to point Ethernet extension over multiple G.SHDSL.bis copper lines
- IEEE 802.3ah EFM 2Base-TL bonding technology
- Compliant with ITU-T G.991.2 standard, TC-PAM 16/32/64/128 line coding
- 1, 2 or 4 pairs G.SHDSL.bis with 5.7Mbps per pairs
- Support extension rate up to 60Mbps over 4 pairs of copper
- CO and CPE mode selectable
- Automatic line rate selection with Line Probe enabled
- Front panel status LED indicators for easy monitoring
- Easy installation with console, Telnet, WEB GUI and SNMP
- Front panel test button for easy loop diagnostic
- Provides extensive diagnostics, including loopback, G.SHDSL.bis performance monitoring
- Easy software upgrade for field-deployed units via TFTP
- DSL line protection for data transmission
- Ethernet switching and bridging with VLAN prioritization and QoS

TAINET's GNTU 764/10x series, which takes advantage of the latest G.SHDSL.bis standard, is a mini-terminal enabling the transport of traffic from Ethernet interface over 15M/30M/60M bps G.SHDSL.bis link.

The GNTU 764/10x series is a EFM G.SHDSL.bis transmission equipment for FE signal extension, aggregate FE channel into a G.SHDSL.bis link. The automatic line rate can be up to 15Mbps over 2-wire cooper line. Embedded Operation Channel (EOC) is built between local and remote sides for system configuration, testing, performance and alarm monitoring of E/FE channel and G.SHDSL.bis link.

SNTU764 is a series of G.SHDSL modems and routers adopting TC-PAM 16/32/64/128 line coding.



### Model

- GNTU 764/102, line card type, G.shdsl.bis NTU, 2-wire, 1 FE
- GNTU 764/104, line card type, G.shdsl.bis NTU, 4-wire, 1 FE
- GNTU 764/108, line card type, G.shdsl.bis NTU, 8-wire, 1 FE
- Interoperability with stand alone GNTU 764/40x Series
  - GNTU 764/402, stand alone, 2-wire, 4 FE
  - GNTU 764/404, stand alone, 4-wire, 4 FE
  - GNTU 764/408, stand alone, 8-wire, 4 FE

### Network Interface - G.SHDSL.bis

- Type: 2, 4 or 8-wire
- Standard: ITU-T G.991.2, ETSI 101 524
- Bonding protocol: IEEE 802.3ah EFM 2Base-TL
- Line rate: n x 64Kbps, n=3~239(2w), 6~478(4w), 12~956(8w)
- Connector: 1xRJ-45
- Line coding: TC-PAM 16/32/64/128
- Impedance: 135 W
- ITU K.21 compliant

### User Interface

- Ethernet type: 10/100 Base-T
- Connector: 1 x RJ-45
- Support 802.3x flow control
- Auto-MDI/MDIX detection, Full duplex / Half duplex support
- Auto-negotiation for speed and duplex

### Ethernet L2 function

- Support 802.1d transparent bridge function
- Supporting Bridge filter function based on source MAC addresses
- Scalable per port bandwidth control (Step = 64K, up to 100M)
- Support 802.3x flow control, and 2K MAC learning address
- Ethernet packet length up to 1664 bytes
- Provide 802.1q VLAN tagging, support 802.1p QoS facility

### Management

- Configuration via craft port VT-100, Telnet, WEB GUI
- Multiple Web browsers supported: IE, Firefox, Chrome
- Support remote management
- Local and Remote loopback for diagnostic
- Support Performance Monitoring function
- Front panel test button for easily loop healthy testing
- Front panel reset to default button

### LED Indicators

- SNTU series:
  - PWR, CO, ALM, TST, L1~L4, ETH LNK/SPD

### Power Requirement

- AC/DC, DC/DC external power adapter (12V, 1A)

### Dimension

- GNTU 764/10x: 84(W) x 168(D) x 24(H) mm

### Operating Environment

- Operation Temperature: 0 °C ~ 50 °C
- Storage Temperature: -20 °C ~ 70 °C

Note:

Features and specifications are subject to change without prior notice.

## Carrier/Service Provider/Enterprise/Utility

